

**FEATURES**

Nippon Paint Gold Paint Emulsion Undercoat is made from premium acrylic emulsion, suitable for both exterior and interior walls. It is designed for surfaces such as plaster, concrete, brickwork, and fibre cement boards. Used as an intermediate coat, it enhances surface coverage and brings out a richer, more lustrous golden tone in the topcoat. It offers excellent weather resistance, resists alkali on cement surfaces, and allows for easy cleaning.

- Outstanding weather resistance
- Excellent protection against mold and algae
- Superior adhesion

**PRODUCT INFORMATION**

Paint type	Acrylic Emulsion Paint
Product type	Exterior and Interior
Film appearance	Matt
Colour	Various colors (see in colorcards)
Recommended substrate	Masonry, plastering, concrete, brick, fiber cement board, etc.
Pack size	1/4 Gallon and 1 Gallon

**TECHNICAL INFORMATION**

Theoretical coverage	30 - 35	m <sup>2</sup> per gallon per coat
	(Actual coverage is dependent on substrate condition and application method)	
No. of coat	1	coat
Touch dry (25-30°C)	30	minutes
Recoat dry (25-30°C)	2	hours
Full cure (25-30°C)	7	days

**REFERENCE STANDARD**

-

**APPLICATION**

Application Method	Brush, Roller or Spray
Diluted by	Clean water
Dilution (%)	Dilute the paint with 10% by volume and mix thoroughly.

**SURFACE PREPARATION**

Old Surface	Remove all loose, defective paint or powdery residues, loose chalk, dust, fungus, algae and foreign matter. (avoid wire brush) Repair cracks, uneven surfaces with Nippon Paint Vinilex Wall Putty Treat any areas affected by fungus growth by scrubbing and allowing the surface to dry completely before painting then apply with Nippon Paint Vinilex Bio Wash 1 coat and leave it until dry.
New Surface	Ensure that the surface is clean and dry it must be free from dirt, greases and other foreign matters. Allow all surfaces to dry completely prior to painting. (At least 28 days) Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 14% measured by protimeter, below 6% by Kett model HI-520 and alkalinity of the walls to be below pH 8.) Repair cracks and uneven surfaces with high-quality materials or decorate the surface appropriately before applying the paint.

**PAINT SYSTEM**

Skim Coat / Old Wall Primer	Nippon Excel Primer (solvent based) 1 coat or Nippon Paint Aqua Sealer (water based) 1 coat
New Wall Primer	Nippon Paint 5100 Wall Sealer 1 coat.
Fresh Cement Wall Primer	Nippon Paint Quick Sealer 1 coat.
Intermediate primer	Nippon Paint Gold Paint Emulsion Undercoat 1 coat.
Top Coat	Nippon Paint Gold Paint Emulsion 2 - 3 coats. **For deep tone, recommend applying the first coat with a lighter tone for good hiding performance.

**HANDLING AND STORAGE**

Storage condition	The product must be stored in a dry, well-ventilated space and keep the container tightly closed. When transporting paint, the product should separately from others. Not recommended to place the product outdoor or exposed to the sun directly and must separately be stored between enamel paint and thinner, which is a flammable substance.
Precipitation	Place the product for a long time may lead the pigment to precipitate at the bottom of the container and can deteriorate over time when not stir product to a homogeneous by using suitable tools, such as an electric drill, air drill, or a stirrer. Therefore, should stir the product to the homogeneous phase before use. If not, the product will cause paint problems e. g. low hiding power or non-equal color shade.
Shelf life	2 years at 30 - 35 °C

**SAFETY PRECAUTIONS**

Precautionary notices are displayed on the container. Use product under well-ventilated area. During use, the product must keep away from the source of ignition and no smoking. Avoiding skin contact or inhale product. In case of contact with the eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from the skin by using soap or water. For others information in terms of health and safety hazards for use of this product, please observe the Safety Data Sheet.

**DISCLAIMER**

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given without prior notice.

**NOTE**

The data are average values for reference only. However, the actual value depends on environmental conditions.